

L6H5

FEATURES

- Aluminium-Alloy IP65 single point load cell
- Colourless anodized
- Suitable for single or double load cell structured platform scales
- Recommended platform size: 200 x 200 mm

AVAILABLE MODELS

Capacity	Accuracy	Full article description
4 kg	C3	L6H5-C3-4kg-0.5B
5 kg	C3	L6H5-C3-5kg-0.5B
6 kg	C3	L6H5-C3-6kg-0.5B
8 kg	C3	L6H5-C3-8kg-0.5B
10 kg	C3	L6H5-C3-10kg-0.5B
20 kg	C3	L6H5-C3-20kg-0.5B
30 kg	C3	L6H5-C3-30kg-0.5B




OIML test certificate no. TC7839 Revision 0
C of C no R60/2000-NL1-10.23


SPECIFICATION

Accuracy class		OIML R60 C3
Output sensitivity (=FS)	mV/V	2.0 ± 0.2
Maximum capacity (E _{max})	kg	4/5/6/8/10/15/20/30
Maximum number of load cell intervals (nLC)		3000
Ratio of minimum LC verification interval Y=E _{max} / V _{min}		15000
Combined error	%FS	± 0.02
Minimum dead load	%FS	0
Safe overload	%FS	120
Ultimate overload	%FS	150
Zero balance	%FS	± 2.0
Excitation, recommended voltage	V	5 ~ 12 (DC)
Excitation maximum	V	18 (DC)
Input resistance	Ω	406 ± 6
Output resistance	Ω	350 ± 3
Insulation resistance	MΩ	≥ 5000 (50VDC)
Compensated temperature	°C	-10 ~ +40
Operating temperature	°C	-35 ~ +65
Storage temperature	°C	-40 ~ +70
Element material		Aluminium
Recommended torque on fixation	N.m	M8: 25
Ingress protection (according to EN 60529)		IP65

DIMENSIONS IN MM



WIRING



- Shielded, 4 conductor cable
- Cable diameter: Φ3.8mm
- Standard cable length: 0.5m
- Shield is not connected to element
- Cable jacket in PVC